



KOAMTAC SKX5™ SmartSled® for Galaxy XCover 5

An All-In-One Data Collecting Solution

Introducing the newest member of the KOAMTAC SmartSled family: the SKX5. The SKX5 is a compact and powerful SmartSled scanning solution designed specifically for use with the Samsung Galaxy XCover 5. With fast and reliable barcode scanning abilities, companion and accessory availability, a rugged IP67 design, and excellent development tools, the SKX5 is the perfect tool for your data collection needs.

Designed

The SKX5 is designed exclusively for the Galaxy XCover 5 and is based on the same modular design as the SKXPro to provide the best barcode scanning experience. This design integrates a 1D/2D Imager conveniently placed at the top of the scanner and offers excellent performance with the ability to read all major barcode symbologies.

Rugged

The SKX5 is IP67-rated and has a 5' drop spec. This means the device is dust tight and water resistant; it's ideal for any environment. Also, every SKX5 is shipped with a protective rubber boot for added grip and protection.

Powered

To best serve high quality information quickly to your team, the SKX5 leverages the display and processing power of the XCover5. Impressive scanning performance is achieved via the N3601 2D imager scan engine with laser aimer. Quickly charge your XCover 5 with KOAMTAC 1-Slot and 5-Slot Charging Cradles with 15W fast charging support. These Charging Cradles charge both the Galaxy XCover 5 with a spare battery or SKX5 companions.

Connected

Powerful scanners require powerful companions. The SKX5 boasts a large number of compatible modular companions including: 0.5W and 1.0W UHF readers, 2,000mAh extended battery, pistol grip with optional 6,000mAh extended battery, and mPOS.

Keyboard wedging and SKX configuration features are included in the complementary SDK for Android, Xamarin, and Cordova. Additionally, receive technical support from top engineers and the development team ensure ease of data collection in any situation.



116 Village Blvd, Suite 305, Princeton, NJ 08540 USA
T: +1-609-256-4700 F: +1-609-228-4373
info@koamtac.com www.koamtac.com

© 2021 KOAMTAC, Inc.
SKX5 - 20211019

Hardware Specifications

Physical Characteristics

Size: 3.07" x 6.38" x 0.91" (77.9 mm x 162 mm x 23 mm)
Weight: 2.77oz (78.5 g)

Electrical Characteristics

Charging: 15W fast charging supported by Charging Cradle
Normal charging via USB Type-C connector

Interfaces

OTG
Power Delivery

User Environment

IP Rating SKX5: IP67
IP Rating SKX5 w companions: IP65
IP Rating SKX5 w 1.0W UHF Reader: IP64
Drop Spec: 5' (1.5 m)
Operating: -4°F to 122°F (-20°C to 50°C)
Storage: -4°F to 140°F (-20°C to 60°C)
Humidity: 5% to 95% (non-condensing)

Performance

Wedging & Synchronization

Transfer to an application
Keyboard wedge function
Add-on prefixes and suffixes
Barcode option selection

Application Generation

SDK for Android, Xamarin, and Cordova

OS Support

Android

Regulatory Conformance

CE, RoHS Compliant
Laser Safety : IEC60825-1:2007 & IEC60825-1:2014, Class II

Scan Engine Specs (20mil Code39)

Scan Range: 1.9" to 29.1" (49 mm to 740 mm)

UHF Specs (for UHF models only)

Supported Standards: EPC Class1 Gen2, EPC Gen2 V2
Nominal Read Range: 20' (6 m) for 1.0W UHF Reader
5' (1.5 m) for 0.5W UHF Reader

Symbologies

Imager (1D): Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, EAN-8, EAN-13, GS1 Composite, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, PosiCode, GS1 Omni, GS1 Limited, GS1 Expanded, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, TCL39, Telepen, Tri-Optic, UPC-A, UPC-E0, UPC-E1

Imager (2D): Aztec Code, Aztec Runes, Codablock F, Code 16K, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, Han Xin Code
Postal Codes: POSTNET, Planet Code, British Post, Canadian Post, Netherlands (KIX) Post, Australian Post, Japanese Post, Chinese Post, Korean Post

Your KDC

Models

SKX5

Compatible Accessories

0.5W UHF Reader
1.0W UHF Reader
Extended Battery
Pistol Grip
SKXSLED-MSRIC
SKXSLED-mPOS
1 and 5-Slot SKX5 Charging Cradles
with Battery Slot(s)



"Designed for Samsung" is a trademark licensed by Samsung to authorized third-party manufacturers for accessories designed to interoperate with a Samsung product.

Samsung is not responsible for the design or manufacture of this accessory, for its operation, or its compliance with safety and regulatory standards.





KOAMTAC SKXPro[®] SmartSled[®] for Galaxy XCover Pro

The Next Generation of SmartSled

A sleek and compact SmartSled scanning solution for the Samsung Galaxy XCover Pro smartphone; the SKXPro outperforms competing industrial PDAs through its aggressive barcode scanning abilities, companion and accessory availability, rugged IP67 design, and excellent development tools.

Designed

The SKXPro, the new barcode sled dedicated to Galaxy XCover Pro, features a brand-new slim design based on KOAMTAC's modular patented SmartSled barcode, RFID, and mPOS sled. The new design integrates a 1D/2D Imager with to ensure the best barcode scanning performance and the ability to read all major barcode symbologies.

Rugged

The SKXPro is IP67-rated and has a 5' drop spec. This means the device is dust tight and water resistant; it's ideal for any environment.

Powered

A 6.3" 2340x1080 Edge-to-Edge display, faster CPU, and more memory allows for quick, high quality information to be served to associates. Aggressive scanning performance is achieved via the N6703 scan engine with laser aimer. Charging Cradles are available in both one-slot and five-slot configurations and charge both Galaxy XCover Pro with a spare battery or SKXPro companions while eliminating extraneous cords. Our Charging Cradles support 15W fast charging.

Connected

The SKXPro is comparable with a breadth of modular companions including: 0.5W and 1.0W UHF readers, 2,000mAh extended battery, pistol grip with 6,000mAh extended battery, and mPOS.

KTSync[®] software with keyboard wedging and KDC configuration features is included for Android and Windows devices. Complementary SDK for Android, Xamarin, and Cordova and technical support from top engineers and the development team ensure ease of data collection in any situation.



116 Village Blvd, Suite 305, Princeton, NJ 08540 USA
T: +1-609-256-4700 F: +1-609-228-4373
info@koamtac.com www.koamtac.com

© 2020 KOAMTAC, Inc.
SKXPro - 20200720

Hardware Specifications

Physical Characteristics

Size: 3.30" x 6.60" x 0.86" (82.6 mm x 168 mm x 21.9 mm)
Weight (XCover Pro + SKXPro): 10.1 oz (285 g)
Weight (SKXPro Only): 2.4 oz (67 g)
Weight (Hand Strap Only): 0.16 oz (4.5 g)

Electrical Characteristics

Charging: 15W fast charging supported by Charging Cradle
Normal charging via USB Type-C connector

Interfaces

OTG
Power Delivery

User Environment

IP Rating SKXPro: IP67
IP Rating SKXPro w companions: IP65
IP Rating SKXPro w 1.0W UHF Reader: IP64
Drop Spec: 5' (1.5 m)
Operating: -22°F to 140°F (-30°C to 60°C)
Storage: -40°F to 158°F (-40°C to 70°C)
Humidity: 5% to 95% (non-condensing)

Performance

Functionality

RAM: 4GB from XCover Pro
ROM: 64GB from XCover Pro, microSD up to 512GB

Wedging & Synchronization

Transfer to an application
Keyboard wedge function
Add-on prefixes and suffixes
Barcode option selection

Application Generation

SDK for Android, Xamarin, and Cordova

OS Support

Android

Regulatory Conformance

FCC, CE, RoHS Compliant
Laser Safety : IEC60825-1:2007 & IEC60825-1:2014, Class II

Scan Engine Specs (20mil Code39)

Scan Range: 1.73" to 31.5" (44 mm to 800 mm)
Motion Tolerance: 19.7 ft/sec (6 m/sec)

UHF Specs (for UHF models only)

Supported Standards: EPC Class1 Gen2, EPC Gen2 V2
Nominal Read Range: 20' (6 m) for 1.0W UHF Reader
5' (1.5 m) for 0.5W UHF Reader

Symbologies

Imager (1D): Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, EAN-8, EAN-13, GS1 Composite, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, PosiCode, GS1 Omni, GS1 Limited, GS1 Expanded, Straight 2 of 5 Industrial, Straight 2 of 5 IATA, TCL39, Telepen, Tri-Optic, UPC-A, UPC-E0, UPC-E1

Imager (2D): Aztec Code, Aztec Runes, Codablock F, Code 16K, Code 49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, Han Xin Code

Postal Codes: POSTNET, Planet Code, British Post, Canadian Post, Netherlands (KIX) Post, Australian Post, Japanese Post, Chinese Post, Korean Post

Your KDC

Models

SKXPro

Compatible Accessories

0.5W UHF Reader
1.0W UHF Reader
Extended Battery
mPOS (PCI/EMV) Coming Soon!
Pistol Grip
1 and 5-Slot SKXPro Charging Cradles with Battery Slot(s)

