



T800 FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Choice of 1D / 2D imager barcode reader, Serial port or Ethernet
- MIL-STD-810H and IP65 certified
- Enhanced Enterprise Security with TPM2.0, Windows Disk Encryption



Office Dock



SnapBack add-on

(Optional) 1D / 2D Imager Barcode Reader, or Serial Port, or Ethernet



Specifications

Generation

G2

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz
- 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" IPS TFT LCD HD (1280 x 800)
Protection film
600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3
Optional: 8GB LPDDR3
128GB eMMC
Optional: 256GB eMMC

Keyboard

Power button
5 tablet programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D / 2D imager barcode reader, Serial port or Ethernet
Optional: SnapBack add-on: Smart Card and contactless HF RFID / NFC reader comboⁱⁱ
Optional: SnapBack add-on: 2nd expanded batteryⁱⁱ
Optional: SnapBack add-on: Smart Card and Magnetic Stripe readerⁱⁱ
Optional: SnapBack add-on: Smart Card and UHF RFID readerⁱⁱ

I/O Interface

FHD webcam x 1
8M pixels auto focus rear camera x 1
Headphone out/Mic-in Combo x 1
DC in Jack x 1
USB 3.2 Gen 1 Type-A x 1
Micro HDMI x 1
Docking Connector x 1
Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel® Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.2)
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband
Optional: 10/100/1000 base-T Ethernet (occupies expansion slot)

Security Feature

TPM 2.0
Optional: SnapBack add-on: Smart Card and contactless HF RFID / NFC reader comboⁱⁱ
Optional: SnapBack add-on: Smart Card and Magnetic Stripe reader
Optional: SnapBack add-on: Smart Card and UHF RFID reader^{iv}

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion battery (7.4V, typical 4200mAh; min. 4080mAh)
LifeSupport™ battery swappable technology (only with SnapBack 2nd expanded battery)

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")
0.88 kg (1.94 lbs)^v

Rugged Feature

MIL-STD-810H certified
IP65 certified
Vibration & 6 feet drop resistant
e-Mark certified for vehicle usage
Optional: ANSI / UL 121201, CSA C22.2 NO. 213ⁱⁱⁱ

Environmental Specification

Temperature^{vi}:
- Operating: -21°C to 50°C / -6°F to 122°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Barcode Managerⁱⁱⁱ
Optional: Absolute Persistence®

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh)
AC Adapter (65W, 100-240VAC)
Capacitive Stylus

Optional:

Carry Bag
Battery (7.4V, typical 4200mAh; min. 4080mAh)
2nd Expanded Battery (14.4V, 2100mAh)
Multi-Bay Charger (Dual Bay)
Multi-Bay Expanded Battery Dock with Adapter (Six Bay)
Multi-Bay Charger (Eight Bay)
AC Adapter (65W, 100-240VAC)
Office Dock AC Adapter (90W, 100-240VAC)
MIL-STD-461 Certified AC Adapter (90W, 115-230VAC)
Vehicle Adapter (120W, 11-32VDC)
Digitizer Pen
Capacitive Stylus
Shoulder Strap (2-point)
Hand Strap
Wrist Strap
Protection Film
Vehicle Cradle
Vehicle Dock
Office Dock

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- i Barcode reader, Serial port, and Ethernet are mutually exclusive options.
- ii All SnapBack add-ons are mutually exclusive options.
- iii 13.56MHz Contactless HF RFID / NFC reader (ISO 15693, 14443 A / B, Mifare and FeliCa™ compliant).
- iv US (902~928MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-63 standards compliant) EU (865~868MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-63 standards compliant)
The maximum read distance of UHF RFID is determined by the design, size of individual tags and environments. Contacting local Getac Sales Representatives for test arrangements is highly recommended.
- v Weight and dimensions vary from configurations and optional accessories.
- vi Tested by a national independent third party test lab following MIL-STD-810H.
- vii Available when barcode reader option is selected.
- viii Available with limited configurations.

T800

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	--
External VGA	--	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	2	4
LAN	1	1
HDMI	--	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--

Getac

Getac (UK) Ltd.

Getac House, Stafford Park 12,
Telford, Shropshire TF3 3BJ, United Kingdom
Tel : +44 (0) 1952 207 222
Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M02Y21UK



T800-EX FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- MIL-STD-810H and IP65 certified
- Enhanced Enterprise Security with TPM2.0, Windows Disk Encryption



SnapBack add-on



Specifications

Generation

G2

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz
- 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" IPS TFT LCD HD (1280 x 800)
Protection film
600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3
Optional: 8GB LPDDR3
128GB eMMC
Optional: 256GB eMMC

Keyboard

Power button
5 tablet programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D / 2D imager barcode reader x1

I/O Interface

FHD webcam x 1
8M pixels auto focus rear camera x 1
Headphone out/Mic-in Combo x 1
DC in Jack x 1
USB 3.0 x 1
Micro HDMI x 1

Communication Interface

Intel® Dual Band Wireless-AC 7265, 802.11ac
Bluetooth (v4.2)
Optional: Dedicated GPS
Optional: 4G LTE mobile broadband

Security Feature

TPM 2.0

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion battery (7.4V, typical 4200mAh; min. 4080mAh)

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")
0.91 kg (2 lbs)

Rugged Feature

MIL-STD-810H certified
IP65 certified
Vibration & 6 feet drop resistant
ATEX & IECEx certified

Environmental Specification

Temperature:
- Operating: -21°C to 50°C / -6°F to 122°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Explosion Protection

ATEX / IECEx zone 2 / 22
Ex II 3G Ex ic IIC T4 Gc
Ex II 3D Ex ic IIIB T130°C Dc

Pre-installed Software

Getac Utility
Getac Barcode Manager®
Getac Camera
Optional: Absolute Persistence®

Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh)
AC Adapter (65W, 100-240VAC)
Capacitive Stylus

Optional:

Battery (7.4V, typical 4200mAh; min. 4080mAh)
2nd Expanded Battery (14.4V, 2100 mAh)
AC Adapter (65W, 100-240VAC)
Digitizer Pen
Capacitive Stylus

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- i Weight and dimensions vary from configurations and optional accessories.
- ii Tested by a national independent third party test lab following MIL-STD-810H.
- iii Available when barcode reader option is selected

T800-EX

Fully Rugged Tablet



Getac

Getac (UK) Ltd.

Getac House, Stafford Park 12,
Telford, Shropshire TF3 3BJ, United Kingdom
Tel : +44 (0) 1952 207 222
Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M10Y20UK