



# Labelmate Product Overview

## Un- and Rewinders



Product	Rewinders	Unwinders	Label dispensers	Label counters
<b>Description</b>	Page 369	Page 369	Page 369	Page 369
<b>Type</b>	Heavy duty and low cost rewinders	Heavy duty unwinders	Automatic label dispensers	Heavy duty label counters
<b>Core diameter</b>	UNI-CAT-1-INCH: 25.4 mm; UNI-CAT, MC-11, MC-11+, TWIN-CAT: 25 mm to 101 mm; UNI-CAT-STANDARD, UNI-CAT-CHUCK, UNI-CAT-10-INCHES, MC-10, MC-10+: 38 mm to 100 mm	UCAT-1: 25 mm to 101 mm; UCAT-3: 25 mm to 101 mm; UCAT-40: 76 mm; UCAT-S: 38 mm to 100 mm	LD-100: 38 mm to 78 mm; LD-200: 38 mm to 76 mm; LD-300: 38 mm to 76 mm	RRC-330: 25 mm to 101 mm; Distri-COUNT: 25.4 mm to 76 mm
<b>Roll diameter</b>	UNI-CAT-STANDARD/-CHUCK/-10-INCHES: 300 mm UNI-CAT-ACH/-1-INCH: 220 mm to 280 mm; MC-10, MC-10+, MC-11, MC-11+, TWIN-CAT: 220 mm	UCAT-1: up to 300 mm; UCAT-3: up to 300 mm; UCAT-40: up to 400 mm; UCAT-S: up to 300 mm	LD-100: up to 220 mm; LD-200: up to 220 mm; LD-300: up to 300 mm	RRC-330: 330 mm; Distri-COUNT: 220 mm
<b>Media width</b>	UNI-CAT: up to 255 mm MC-10, MC-10+: up to 125 mm; MC-11, MC-11+: up to 115 mm; TWIN-CAT: up to 270 mm; S-100: 170 mm; S-200: 255 mm	UCAT-1: up to 255 mm; UCAT-3: up to 255 mm; UCAT-40: up to 170 mm; UCAT-S: up to 155 mm	LD-100: up to 115 mm; LD-200: up to 165 mm; LD-300: up to 218 mm	RRC-330: 152 mm; Distri-COUNT: max. 115 mm
<b>Speed</b>	UNI-CAT: up to 125cm/sec., TWIN-CAT: up to 125 cm/sec., MC-10, MC-10+, MC-11, MC-11+: up to 50 cm/sec., S-100/S-200: 125 cm/sec., limited by printer	UCAT-3, UCAT-40: up to 125 cm/sec.; UCAT-1, UCAT-S: same as printer	LD-100: 11 cm/sec.; LD-200: 11 cm/sec.; LD-300: 11 cm/sec.	RRC-330: 72 to 235 cm/sec.; Distri-COUNT: n/a
<b>Features/options</b>	Optional: tension arm, quick chucks, version with geared motor, foot switch, adjustable reel tension, potentiometer, label slitter, zero tension loop	Optional: tension arm, quick chucks	Optional: counter (pre-settable), core expansion, battery, supports transparent and dark labels (LD-100-U, LD-200-U)	Optional: encoder for length measurement + Battery pack, Sensor for transparent and black labels
<b>Weight</b>	5.3 kg to 18.6 kg	6 kg to 13 kg	6 kg to 8 kg	16 kg to 20 kg
<b>Dimensions (W x D x H)</b>	UNI-CAT-STANDARD: 300 x 350 x 320 mm UNI-CAT-CHUCK: 300 x 385 x 320 mm UNI-CAT-ACH: 280 x 310 x 310 mm UNI-CAT-10-INCHES: 300 x 455 x 320 mm UNI-CAT-1-INCH: 220 x 350 x 280 mm; MC-10, MC-10+, MC-11, MC-11+: 305 x 220 x 195 mm; TWIN-CAT: 370 x 180 x 470 mm; S-100: 280 x 355 x 250 mm; S-200: 280 x 435 x 250 mm	UCAT-1: 350 x 300 x 320 mm; UCAT-3: 350 x 300 x 320 mm; UCAT-40: 450 x 400 x 460 mm; UCAT-S: 365 x 300 x 320 mm	LD-100: 200 x 210 x 270 mm; LD-200: 200 x 270 x 270 mm; LD-300: 250 x 300 x 295 mm	RRC-330: 330 x 830 x 330 mm; Distri-COUNT: 232 x 295 x 222 mm
<b>Warranty</b>	5 years (SR-100/SR-200: 3 years)		3 years	