

iiyama Product Overview

Touchmonitors



Product	T15XX	T16XX	T17XX	T19XX	T22XX	T23XX	T24XX	T27XX
Display size	15" (38.1 cm)	15.6" (39.5 cm cm)	17" (43 cm)	19" (48 cm)	21.5" (55 cm)	23" (58.4 cm)	23.6" (60 cm)	27" (68.6 cm)
Aspect ratio	4:3	16:9	5:4	5:4	16:9	16:9	16:9	16:9
Max. resolution	1,024 × 768 pixels	1,366 × 768 pixels	1,280 × 1,024 pixels	1,280 × 1,024 pixels	1,920 × 1,080 pixels	1,920 × 1,080 pixels	1,920 × 1,080 pixels	1,920 × 1,080 pixels
Touch technology	Resistive, projective capacitive multi-touch, SAW	Projective capacitive	Resistive, projective capacitive multi-touch, SAW	Resistive, projective capacitive multi-touch, SAW	Projective capacitive multi-touch, optical multi-touch	Projective capacitive multi-touch	Optical multi-touch	Projective capacitive multi-touch
Touch interface	USB, RS-232 / USB	USB	USB, RS-232 / USB	USB, RS-232 / USB	USB	USB	USB	USB
Brightness	Up to 340 cd/m ²	255 cd/m ²	Up to 230 cd/m ²	Up to 230 cd/m ²	Up to 225 cd/m ²	Up to 215 cd/m ²	Up to 260 cd/m ²	Up to 300 cd/m ²
Contrast	Up to 800:1	500:1	Up to 1,000:1	Up to 1,000:1	Up to 3,000:1	1,000:1	1,000:1	3,000:1
Connection	VGA, HDMI, Displayport	VGA, HDMI, DisplayPort, USB (HUB)	VGA, HDMI, Displayport	VGA, HDMI, Displayport	HDMI, DVI, VGA	HDMI, DVI, VGA	HDMI, DVI, VGA	HDMI, DVI, VGA
Colour (housing)	Black, white	Black	Black, white	Black, white	Black	Black	Black	Black
Warranty	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years

Interactive Digital Signage (IDS)



Product	TE5503	TE6504/TE7504/TE8604	TF9803
Display size	55" (138.8 cm)	TE6504: 64.5" (163.9 cm) TE7504: 74.5" (189.3 cm) TE8604: 85.6" (217.4 cm)	98" (247.7 cm)
Aspect ratio	16:9	16:9	16:9
Max. resolution	3,840 × 2,160 pixels	3,840 × 2,160 pixels	3,840 × 2,160 pixels
Touch technology	Infrared	Infrared	Infrared
Touch interface	USB	USB	USB
Brightness	350 nits	350 nits	350 nits
Contrast	1,200:1	1,200:1	4,000:1
Interfaces	VGA, HDMI, RS-232c, Ethernet, USB	VGA, 3x HDMI, DisplayPort, 5x USB, 1x USB-C, WiFi, RS-232c, Ethernet, Audio	VGA, 3xHDMI, RS-232c, Ethernet, Audio, 6x USB
Colour (housing)	Black	Black	Black
Warranty	3 years	5 years (with 16/7 use)	5 years



Product	SPC5801BC
Type	Slot PC
Operating system	Win 10 IoT Enterprise SAC high-end (64-bit)
CPU	Intel Core i5-8400
Chipset	Intel H310
RAM	8 GB DDR4
SSD	256 GB M.2
Connection	VGA, HDMI, DisplayPort, USB
Network	Ethernet, Wi-Fi 802.11ac
Audio	Integrated high definition audio stereo
Power supply	Internal, AC 100-240V, 95W, 1.35W stand-by
Dimensions W x H x D/ weight	263.4 × 32.2 × 246.1 mm / 1.9 kg

Open-Frame LCDs



Product	TF1015-TF3215	TF1534-TF2234	TF2738-TF6538	TF3239-6539
Display size	31.5", 23.8", 21.5", 15", 10.1"	21.5", 19", 17", 15.6", 15"	65", 55", 48.5", 43", 27"	31.5"; 43"; 49"; 55"; 65"
Aspect ratio	16:10, 16:9, 4:3	16:9, 5:4, 4:3	16:9	16:9
Max. resolution	1,920 × 1,080 pixels, 1,280 × 800 pixels, 1,024 × 768 pixels	1,920 × 1,080 pixels, 1,366 × 768 pixels, 1,280 × 1,024 pixels, 1,024 × 768 pixels	3,840 × 2,160 pixels, 1,920 × 1,080 pixels	TF3239: 1,920 × 1,080 pixels TF4339: 1,920 × 1,080 pixels TF4939: 3,840 × 2,160 pixels TF5539: 3,840 × 2,160 pixels TF6539: 3,840 × 2,160 pixels
Touch technology	Projective capacitive	Projective capacitive	Projective capacitive	Projective Capacitive
Touch interface	USB	USB	USB	USB
Brightness	460 cd/m ² , 450 cd/m ² , 425 cd/m ² , 315 cd/m ² , 300 cd/m ²	360 cd/m ² , 330 cd/m ² , 315 cd/m ² , 305 cd/m ² , 300 cd/m ² , 250 cd/m ² , 225 cd/m ²	420 cd/m ² , 380 cd/m ² , 255 cd/m ²	TF3239: 420 nits TF4339: 340 nits TF4939: 420 nits TF5539: 420 nits TF6539: 420 nits
Contrast	3,000:1, 1,300:1, 1,000:1, 800:1	1000:1, 700:1, 500:1	3,000:1, 1,100:1	TF3239: 3,000:1 TF4339: 4,000:1 TF4939: 1,100:1 TF5539: 1,100:1 TF6539: 1,100:1
Connection	VGA, HDMI, DisplayPort, Audio	USB, RS-232, Ethernet, VGA, HDMI, DisplayPort, Audio	RS-232, Ethernet, VGA, DVI, HDMI, DisplayPort, Audio	VGA, 2x HDMI, DisplayPort, Audio, RS-232c, Ethernet
Colour (housing)	Black	Black	Black	Black
Warranty	3 years	3 years	3 years	3 years

IDS displays are not available in the UK

iiyama Product Overview

Non-Touch Large Format Displays



Product	LH3252	LH4352	LH5052	LH5552	LH6552
Display size	31.5" (80 cm)	42.5" (108 cm)	49.5" (125.7 cm)	54.6" (138.8 cm)	64.5" (163.9 cm)
Aspect ratio	16:9	16:9	16:9	16:9	16:9
Max. resolution	1,920 × 1,080 pixels	3,840 × 2,160 pixels	3,840 × 2,160 pixels	3,840 × 2,160 pixels	3,840 × 2,160 pixels
Response time	8 ms	8 ms	8 ms	8 ms	8 ms
Display colour	16.7 m, 8bit	1.07 bn (8 bit + FRC)	1.07 bn (8 bit + FRC)	1.07 bn (8 bit + FRC)	1.07 bn (8 bit + FRC)
Brightness	400 nits	500 nits	500 nits	500 nits	500 nits
Contrast	1,200:1	1,200:1	4,000:1	5,000:1	1,200:1
Connection	VGA, DVI, 2× HDMI	VGA, DVI, 3× HDMI	VGA, DVI, 3× HDMI	VGA, DVI, 3× HDMI	VGA, DVI, 3× HDMI
Colour (housing)	Black	Black	Black	Black	Black
Warranty	3 years	3 years	3 years	3 years	3 years

Non-Touch Monitors



Product	XB/B22XX	XB/B24XX	XB/B27XX	XUB34XX
Display size	XUB22XX: 21.5" (54.6 cm) B22XX: 22" (56 cm)	23.8" (60 cm)	27" (68.5 cm)	34"
Aspect ratio	XUB22XX: 16:9 B22XX: 16:10	16:9	16:9	21:9
Max. resolution	XUB22XX: 1,920 × 1,080 pixels B22XX: 1,680 × 1,050 pixels	1,920 × 1,080 pixels	1,920 × 1,080 – 3,840 × 2,140 pixels	3,440 × 1,440 pixels
Response time	XUB22XX: 4 ms B22XX: 5 ms	1 ms–5 ms	1 ms–4 ms	4 ms
Display colour	16.7 m (sRGB: 99 %; NTSC: 72 %)	16.7 m (sRGB: 99 %; NTSC: 72 %)	16.7 m–1.07 bn	1.07 bn
Brightness	250 nits	250 nits	250–350 nits	320 cd/m ²
Contrast	XUB2294: 3,000:1 XUB2292: 1,000:1 B2280: 1,000:1	1,000:1	1,000:1	1,000:1
Connection	XUB22XX: VGA, HDMI, DisplayPort B22XX: VGA, DVI	VGA, HDMI, Displayport	VGA, DVI, HDMI, Displayport	HDMI, DisplayPort, USB (HUB), audio
Colour (housing)	Black	Black or white	Black or white	Black
Warranty	3 years	3 years	3 years	3 years