

PrehKeyTec Product Overview

Programmable Keyboards



Product	MCI 30	MCI 60 / MSI 60	MCI 84	MCI 96	MCI 128	MW 820
Number of keys	30	60	84	96	128	85
Keyboard layout	6 x 5	5 x 12 / 6 x 10	7 x 12	6 x 16	8 x 16	Alphanumeric
Driver	OPOS, JavaPOS	OPOS, JavaPOS	OPOS, JavaPOS	OPOS, JavaPOS	OPOS, JavaPOS	-
Interface	USB	USB	USB	USB	USB	USB
OS compatibility	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC	DOS, Linux, Windows, Mac
Status LED	4	4	4	4	4	2
Magnetic stripe reader	Optional	Optional	Optional	Optional	Optional	-
Chip card reader	-	-	-	Optional	Optional	IP54
OCR reader	-	-	-	-	-	-
Fingerprint reader	Optional	Optional	Optional	Optional	Optional	-
Glide pad	-	Optional	Optional	Optional	Optional	Integrated
Key lock	-	Optional	Optional	Optional	Optional	-
Colour	Black, white	Black, white	Black, white	Black, white	Black, white	Black
Warranty	3 years	3 years	3 years	3 years	3 years	1 year

Integrated Input Devices and Readers



Product	MCI 111	MCI 3100
Number of keys	Standard	Standard
Keyboard layout	QWERTZ, QWERTY	QWERTZ, QWERTY
Driver	Windows, OPOS, JavaPOS	OPOS, JavaPOS
Interface	USB	USB
OS compatibility	Windows, Linux	DOS, Linux, Windows, MAC
Status LED	4	4
Magnetic stripe reader	Integrated	Optional
Chip card reader	-	Optional
OCR reader	Integrated	-
Fingerprint reader	-	Optional
Glide pad	Optional	Optional
Key lock	-	Optional
Colour	Black, white	Black, white
Warranty	3 years	3 years

Programmable Silicone Keyboards



Product	SIK 21	SIK 65	SIK 2500	HospiTouch	GIK 2700
Keyboard layout	Numeric	QWERTZ, QWERTY	QWERTZ, QWERTY	QWERTZ, QWERTY	QWERTZ, QWERTY
Number of keys	21	65	Standard	Standard	Standard
Interface	USB	USB	USB	USB	USB
OS compatibility	Windows, Linux, USB HID	Windows, Linux, USB HID	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC	DOS, Linux, Windows, MAC
Status-LED	-	-	2	3	3
Glidepad	-	-	-	Integrated	Integrated
Temperature	-30° C to +50° C	-30° C to +50° C	-10° C bis +50° C	-10° C bis +50° C	-10° C bis +50° C
Environmental sealing	IP66	IP66	IP65	IP65	IP65
Colour	Black	Black	Black	White	Black
Warranty	1 year	1 year	3 years	3 years	3 years

Glass Keyboards



Stand-alone Reader



Product	ML 2
Reading types	Magnetic stripe reader, OCR
Interface	USB
MSR	Tracks: 1, 2, 3, ISO 7810, ISO 7811
OCR	Reads machine readable documents, according to ICAO9303
RFID	-
Fingerprint	-
Operating Temperature	5 - 40° C
Dimensions	77.5 x 64.5 x 281 mm
Options	-