


# Evolis Product Overview

## Desktop Printers



Product	Badgy200	Zenius	Primacy	Avansia	Quantum	Securion
<b>Description</b>	Page 276	Page 276	Page 276	Page 276	Page 277	Page 277
<b>Resolution</b>	12 dots/mm (300 dpi)	11.8 dots/mm (300 dpi)	11.8 dots/mm (300 dpi)	23.6 dots/mm (600 dpi)	11.8 dots/mm (300 dpi)	11.8 dots/mm (300 dpi)
<b>Printable sides</b>	Single-sided	Single-sided	Single or double-sided	Single and double-sided	Single and double-sided	Single and double-sided
<b>Card format</b>	CR-80 – ISO 7810 (53.98 x 85.60 mm)	CR-80 – ISO 7810 (53.98 x 85.60 mm)	CR-80 – ISO 7810 (53.98 x 85.60 mm)	CR-80 – ISO 7810 (53.98 x 85.60 mm)	CR-80 – ISO 7810 (53.98 x 85.60 mm)	CR-80 – ISO 7810 (53.98 x 85.60 mm)
<b>Print speed</b>	Up to 325 cards/hour	Up to 500 cards/hour	Up to 850 cards/hour	Up to 144 cards/hour	Up to 1000 cards/hour	Up to 120 cards/hour
<b>Card thickness</b>	0.50 to 0.76 mm (20 to 30 mil)	0.25 to 0.76 mm	0.25 to 1.25 mm	0.76 mm (30 mil)	0.76 to 1 mm	0.25 to 1 mm
<b>Encoding options</b>	No	Magnetic stripe, contact and contactless smart cards	Magnetic stripe, contact and contactless smart cards	Magnetic stripe, contact and contactless smart cards	Magnetic stripe, contact and contactless smart cards	Magnetic stripe, contact and contactless smart cards
<b>Print mode</b>	Color sublimation, monochrome retransfer printing	Dye sublimation, monochrome thermal transfer printing	Dye sublimation, monochrome thermal transfer printing	Color dye sublimation, resin monochrome retransfer printing	Dye sublimation, monochrome thermal transfer printing	Dye sublimation, monochrome thermal transfer printing
<b>Laminator</b>	No	No	No	No	No	Yes
<b>Interface</b>	USB	USB, USB/Ethernet	USB/Ethernet, USB/Wi-Fi	USB/Ethernet	USB/Ethernet	USB/Ethernet
<b>Weight</b>	1.7 kg	3.3 kg	4 kg	20 kg	21.7 kg	15.4 kg
<b>Power supply</b>	100–240 V AC, 50–60 Hz, 1.8 A	100–240 V AC, 50–60 Hz, 1.8 A	100–240 V AC, 50–60 Hz, 1.8 A	90–125 V AC, 220–240V, 50-60 Hz	100–240 V AC, 50–60 Hz, 2 A	100–240 V AC, 50–60 Hz, 2 A
<b>Warranty</b>	1 year	2 years	3 years	3 years and lifetime warranty on print head	1 year	2 years
<b>Dimensions (HxWxD)</b>	147 x 200 x 276 mm	205 x 315 x 195 mm	205 x 381 x 247 mm	436 x 340 x 297 mm	300 x 850 x 215 mm	263 x 563 x 275 mm

## Signature Pads



Product	SIG100	SIG200
<b>Description</b>	Page 277	Page 277
<b>Display size</b>	10.5 cm (4") LCD	12.7 cm (5") LCD
<b>Resolution</b>	320 x 160 pixels	640 x 480 pixels
<b>Active signing area</b>	95 x 47 mm	100 x 75 mm
<b>Supported OS</b>	Windows XP 32/64, 7 32/64, 8 32/64, 10 32/64, Server 2003, 2008, Linux	
<b>Interface</b>	USB 2.0 (HID)	
<b>Dimensions (HxWxD)</b>	10 x 160 x 120 mm	15 x 191 x 180 mm
<b>Weight</b>	200 g	356 g
<b>Certification</b>	EC, FCC, RoHS, EN 60950-1, EN 61000-6-1, EN 61000-6-3	
<b>Delivery content</b>	Signature pad, captive USB cable, stylus, stylus holder (Sig200)	
<b>Warranty</b>	2 years	

Not available in Egypt.

### Original ribbons, cards & cleaning sets

Reduce the cost per card without compromising print result quality.



### Original options

Expand the usage of your printer with an optional laminator, encoding kit, or upgrades for double-sided printing.



### Complete your ID badge solution

Extensive line of ID accessories from badge holders to custom lanyards.



### cardPresso Software

Evolis Zenius, Primacy, Quantum and Avansia card printers are delivered with cardPresso software, the ultimate tool for professional card design.



Not available in Egypt.