



Glancetron K900

Ideal for cramped spaces

- Multi-faceted complete POS with a compact footprint
- Bezel-free touch 15" (38.1 cm) screen
- Powerful Intel Celeron processor with 2.4 GHz and 2 GB RAM
- Space-saving peripherals: many devices in one
- Practical: rear-side integrated receipt printer and customer display

Specifications

System	CPU	Celeron G530 2.4GHz, L2 Cache-2 MB
	Chipset	Intel H61
	System memory	2 GB DDR3 SO-DIMM Slot, up to 8 GB
	Hard disk drive	320 GB HDD (2,5")
	Audio	Internal speakers
Supported operating systems		XP, 7, POSReady2009, POSReady7, WES2009 ,WES7
Display	Graphics chip	Intel HD
	Screen size	15" / TFT, 38.1 cm
	Resolution	1024 x 768 pixels
	Brightness	250 cd/m ²
	Touch screen	5-wire resistive bezel free
Interfaces	USB 2.0	5 (4x back, 1x front)
	Serial/COM	2x DB-9 (COM 2/3), 1x RJ45 (COM 1),+5V/12V selectable
	LAN	1x Gigabit
	VGA	1x DB-15 VGA Interface
	PS/2	1x PS/2 port (default at keyboard)
	Cash drawer port	1x RJ11 (+12V or +24V selectable) (default at +12V)
	Audio	1x line out
PSU	Power adapter	External power supply, 24V (6.25A)
Miscellaneous	Dimensions (WxDxH)	385 x 188 x 313 mm
	Operating temperature	0°C to 35°C
	Certifications	FCC, UL, CE
	Mounting options	VESA mount (100 mm x 100 mm)
Printer	Printing method	Direct thermal
	Print speed	200 mm/s
	Media width	80 mm
	Print width	72 mm
	Resolution	8 dots/mm (203 dpi)
Customer Display	Display	VFD, 2 lines with 20 characters each
	Brightness	500 ~ 1000 cd/m ²
	Commands mode	LD220, EPSON POS (default), AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAY, LOGIC Control
	Character type	95 alphanumeric, 32 international characters
Options	Magnetic stripe reader	Tracks 1, 2, 3, LoCo, HiCo
	iButton reader	Dallas, +5V D.C



Your partner