

L-420

METAPACE L-420 Powerful label printer

Technical specifications

PRINT

Printing method	Direct thermal
Print width	max. 108 mm
Print length	6 – 1000 mm
Print speed	max. 178 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

MEDIA

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 – 110 mm
Roll diameter	max. 130 mm
Core diameter	25.4 – 38.1 mm
Media strength	0.06 – 0.2 mm

ELECTRONICS

Memory	Flash: 128 MB, RAM: 64 MB DDR2
Interfaces	USB 2.0, Serial, Parallel, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A, Energy Star
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

SOFTWARE

Emulation	EPL (compatible), EPL II (compatible), ZPL (compatible), ZPL II (compatible), SLCS
Drivers	Windows 2000, XP, 2003 Server, Vista, Windows 7, Linux, Mac OS
Labeldesigner	Metapace Label Designer Software

SPECIFICS

Options	Auto-Cutter, Dispenser, Ethernet, WiFi, external media holder
---------	--

WARRANTY

Period	24 months
--------	-----------

HOUSING

Dimension (WxHxD)	194 × 171 × 243 mm
Weight	2.2 kg

Highlights

- + Direct thermal label printer for high throughput
- + Max speed: 178 mm/sec. at 203 dpi
- + Triple interface; ZPL, ZPLII, EPL, EPLII
- + Everything included: power supply, connection cable, cleaning pen, design software, etc.
- + Optionally available: peeler, auto cutter, Wi-Fi dongle, 300 dpi version



Drivers
by Seagull™

