

## Panasonic reliability - now in small packages...

The Panasonic JS-790WS proves that good things really do come in small packages. Purpose-built design with the proven reliability you've come to expect from Panasonic, the 790WS is the next big thing in point of sale systems (POS).



JS-790WS

### Compact

- Save valuable counter space with the compact design of the 790WS. Even the tightest front counter can accommodate the sleek shape of the Panasonic 790WS.
- The "all-in-one" design of the 790WS eliminates the clutter of additional hardware giving you a clean look that also saves space.
- Make the most of your front counter real estate by taking advantage of the 790WS's rear-facing point of purchase display. Promoting special menu items is now easier than ever!

## Innovative

- The adjustable, dual back light LCD display provides high resolution, high contrast images for faster, more accurate order taking.
- No moving parts gives the 790WS much higher reliability than other workstations or PCs that have hard disk drives (HDD) and fans.
- Optional internal uninterrupted power supply (UPS) ensures smooth system shutdown and recovery in the event of a sudden power loss.
- Modular design features field replaceable compact flash card, and an easily accessible UPS battery for fast, easy maintenance if needed.

## Durable

- Keep your restaurant looking clean and new with the Panasonic 790WS. The durable plastic casing resists dust, dirt and grease build-up, giving your front counter a friendly and clean face.
- Accidents happen but they won't stop the Panasonic 790WS. With a spill resistant design, the 790WS can withstand even the wettest mistakes.
- Free of moving parts, the 790WS is XP embedded with no hard drive, making it an outstanding choice for supreme reliability and durability.

## Supportable

- A field replaceable Compact Flash (CF) card allows you to easily maintain your workstation and save money on costly service visits.
- Save the time and headache of a lengthy workstation set up. With the help of your back-office PC, configuring the 790WS is as easy as inserting a blank CF card and answering a few simple questions.
- Rest easy, your valuable store data is dually maintained in your 790WS and back-office PC, allowing easy data restoration when necessary.

## Specifications

OS	Window XP embedded
CPU	VIA 800MHz
Memory	256MB standard (Max. 512MB)
Display	12.1" TFT / 800 x 600 SVGA
Touch Panel	Resistive
Compact Flash Memory Card	512MB CF memory card (HDD option)
LAN	10/100 base-T
Power Supply	Built-in
UPS Battery	Built-in
Port	
Serial	2 ports (additional 2 ports option)
VGA	1 port
LAN	1 port
USB(2.0)	2 ports
Drawer	1 port (additional 1 port option)
Dimension (mm)	W: Footprint 250, Display unit 310 D: 250, H: 337(with rubber foot)
Weight (Kg)	7.0

## Options

Magnetic Card Reader	JS-790MG-020
Rear Display	JS-790RD-010
Optional I/O Board	JS-790CB-010
Display Protection Sheet	JS-790DS-010
Cash Drawer	JS-750CD
Compact Flash Memory Card	JS-790CF5121 (1 piece) JS-790CF5125 (5 pieces)



# Panasonic®

**Panasonic System Solutions Company**  
Unit Company of Panasonic Corporation of North America, Information Systems - POS  
1707 N. Randall Rd, Elgin IL, 60123-7847  
Phone:1-847-468-4600 Fax:1-847-468-4555

**Panasonic Canada Inc.**  
5770 Ambler Drive, Mississauga, ON, L4W 2T3  
Phone:1-905-238-2267 Fax:1-800-663-5192

**Panasonic de México,S.A de C.V.**  
Amores 1120 Col.Del Valle  
C.P.03100 México, D.F., México  
Phone:52(55)5488-1000 Fax:52(55)5575-6763

**Panasonic Deutschland GmbH**  
Winsbergring 15,22525 Hamburg Germany  
Phone:+49(0)40-8549-2627 Fax:+49(0)40-8549-3111

**Panasonic Business Systems U.K.**  
Panasonic House, Willoughby Road.  
Bracknell, Berks, RG12 8FP  
Phone:+44(0)1344-476-514 Fax:+44(0)1344-853-705

**Panasonic Australia Pty. Ltd.**  
Austlink Corporate Park 1 Garigal Road  
Belrose NSW 2085. Australia  
Phone:2-9986-7384 Fax:2-9986-7575

**Panasonic System Solutions Company Matsushita Electric Industrial Co.,LTD**  
4-3-1 Tsunashima-higashi, Kohoku-ku,  
Yokohama City 223-8639, Japan  
Phone:+81-45-544-3447 Fax:+81-45-544-3448