

# STANDS, HOLDERS, CORDLESS BASES, AND ACCESS POINTS



#### HOLDER-010-U

#### Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



#### STND-30R00-011-4

## Rigid Presentation Stand

Stand: gray, 5" rigid rod, weighted base, Granit cradle.



#### STND-33F00-012-4

#### Flexible Presentation Stand

Stand: gray, 9"flexible rod, weighted base, Granit cradle.



#### VMHOLDERK

#### Vehicle mount holder

Vehicle mount kit contains vehicle mount forked holder, adjustable arm with ball joints, and mounting hardware



#### AP-05-100BT-07N

#### Bluetooth Access Point

Access point for Granit XP and Granit 1981i scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



AP-100BT-07N

#### Bluetooth Access Point

Access point for Granit XP scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



TOOLBAL

#### Take-Up Reel/Tool Balancer

Suspension reel commonly used for scanner mounting/retention on vehicles and in fixed locations.

# CHARGE AND COMMUNICATION BASES, CHARGERS AND BATTERIES





#### **Smart Battery Pack**

Battery: Lithium-ion battery for Xenon XP 1952cordless scanners.



#### CCB22-100BT-03N

#### Granit XP Charge/Communication Base

Base: Charge and communication. Class 1 Bluetooth. 100m (300'), up to 3 scanners can be connected. Compatible with RS232/USB/KBW cables (sold separately).



COB22

#### Granit XP Charge Only Base

Base: Charge only. Only one scanner can be connected at a time. Power supply required and must be purchased separately.



#### MB4-BAT-SCN01NAD0

## 4-Bay Battery Charger – Desk Mount

4-bay battery charger (NA) for use with Granit and Xenon Lithiumion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).



#### MB4-BAT-SCN01NAW0

#### 4-Bay Battery Charger - Wall Mount

4-bay battery charger (NA) for use with Granit and Xenon lithium-ion batteries, NA wall-mount power supply (PS-050- 4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

### **HEATERS**



520L-12-S3

#### Scanner Heater with Cable Retractor

12V heater for Granit scanners in freezer environments



520L-24-S3

#### Scanner Heater with Cable Retractor

24V heater for Granit scanners in freezer environments



520L-3648-S3

## Scanner Heater with Cable Retractor

36-48V heater for Granit scanners in freezer environments



521L-12-S3

#### Scanner Heater

12V heater for Granit scanners in freezer environments



521L-3648-S3

#### Scanner Heater

36-48V heater for Granit scanners in freezer environments

### CABLES AND POWERSUPPLIES

CBL-020-300-C00

RS-232 Power Cable

Cable: RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.

CBL-020-300-C00-01

RS-232 Power Cable

Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.

CBL-020-300-C00-02

RS-232 Power Cable

Cable, Industrial (for freezer temps): RS-232 (5Vsignals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.

CBL-020-500-C00

RS-232 Power Cable

Cable: RS-232 (+5V signals), black, DB9 female, 5 m (16 ft), coiled, external power with option for host power on pin 9.

CBL-1020-300-C00

RS-232 Power Cable

Cable: RS-232 (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9.

CBL-220-300-C00

RS-232 Power Cable

Cable: RS-232 (5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.

CBL-320-300-C00

RS-232 Power Cable

Cable: RS-232 (+/- 12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.

CBL-500-300-C00

**USB Power Cable** 

Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power.

CBL-500-300-S00 USB Power Cable

Cable: USB, black, Type A, 3m (9.8'), straight,

5V host power.

CBL-500-300-S00-01

USB Power Cable

Cable, Industrial (for freezer environments) USB, black, Type A, 3m (9.8'), straight, 5V host power.

CBI -500-500-C00

**USB Power Cable** 

Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power.

CBL-501-300-S00

**USB Power Cable** 

Cable: USB Granit scanner cable, compatible with USB D9 connectors on VM series docks. CBI -503-300-C00

**USB Power Cable** Cable: USB, black, 12V

locking, 3m (9.8'), coiled, 5V host power.

CBI -503-300-S00

**USB Power Cable** 

Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power. CBI -503-500-C00

**USB Power Cable** 

Cable, USB, black, 12V locking, 5m (16.4'), coiled, 5V host power.

CBL-720-300-C00

**KBW Power Cable** 

Cable: KBS, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power.

CBL-720-370-C00 PS-2 Power Cable

Cable: PS-2 Keyboard Wedge, Coiled, 5V.

MX009-3MA8SN

**USB Power Cable** 

Cable: USB POS, Type A, Straight, Black, No PowerL 46-00525-6

Power Supply - NAPlug

Power Supply: NA plug, 1.0A@ 5.2V DC, 90-255V AC @ 50-60 Hz.

46-00526

Power Supply - EUPlug

Power Supply: EU plug, 1.0A@ 5.2V DC, 90-255V AC @ 50-60 Hz.

46-00528

Power Supply - AUPlug

Power Supply: AU plug, 1.0A@ 5.2V DC, 90-255V AC @ 50-60 Hz.

46-00529

Power Supply - CN Plug

Power Supply: CN plug, 1.0A@ 5.2V DC, 90-255V AC @ 50-60 Hz.

> THE UTURE

