



**24" IPS 3-side borderless monitor with height adjustable stand**


Stylish edge-to-edge design makes the ProLite XUB2493HS perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort, make this 24" monitor a great choice for both multi-monitor configuration and office applications.

Available also with fixed stand : [ProLite XU2493HS-B6](#)



**IPS Technology**

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.



**HAS (150mm) + PIVOT**

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

## 01 DISPLAY CHARACTERISTICS

|                             |   |
|-----------------------------|---|
| <b>Design</b>               | 3-side borderless   |
| <b>Diagonal</b>             | 23.8", 60.5cm   |
| <b>Panel</b>                | IPS panel technology LED, matte finish                                |
| <b>Native resolution</b>    | 1920 x 1080 @100Hz (2.1 megapixel Full HD)                            |
| <b>Aspect ratio</b>         | 16:9  |
| <b>Panel brightness</b>     | 250 cd/m <sup>2</sup>   |
| <b>Static contrast</b>      | 1300:1  |
| <b>Advanced contrast</b>    | 80M:1   |
| <b>Response time (MPRT)</b> | 0.5ms   |
| <b>Viewing zone</b>         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| <b>Colour support</b>       | 16.7mIn (sRGB: 96%; NTSC: 72%)  |
| <b>Horizontal Sync</b>      | 30 - 115kHz   |
| <b>Viewable area W x H</b>  | 527 x 296.5mm, 20.7 x 11.7"   |
| <b>Pixel pitch</b>          | 0.275mm   |
| <b>Colour</b>               | matte, black  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                            |   |
|----------------------------|---|
| <b>Signal input</b>        | HDMI x1 (v. 1.4)<br>DisplayPort x1 (v. 1.2) |
| <b>HDCP</b>                | yes   |
| <b>Headphone connector</b> | yes   |

## 03 FEATURES

|                              |  |
|------------------------------|--|
| <b>Blue light reducer</b>    | yes  |
| <b>Flicker free</b>          | yes  |
| <b>Adaptive Sync support</b> | yes  |
| <b>Extra</b>                 | i-style Colour   |
| <b>OSD languages</b>         | EN, DE, FR, IT, RU, JP, CZ, NL, PL   |
| <b>Control buttons</b>       | Power, Menu, + / Volume, - / Eco, Signal / Exit  |
| <b>User controls</b>         | picture adjust (brightness, contrast, i-Style colour, ACR, Eco, OD, X-res technology), colour settings (gamma, RGB range, colour temp.), image settings (video mode adjust, blue light reducer, sharp and soft, MBR, AdaptiveSync), OSD (OSD H. position, OSD V. position, OSD time, OSD background, OSD rotate, language, display information), extra (reset, DDC / CI, signal select, LED, opening logo) |
| <b>Speakers</b>              | 2 x 2W   |
| <b>Convenience</b>           | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX  |

## 04 MECHANICAL

|                                     |  |
|-------------------------------------|--|
| <b>Display position adjustments</b> | height, pivot (rotation), swivel, tilt |
| <b>Height adjustment</b>            | 150mm                                  |
| <b>Rotation (PIVOT function)</b>    | 90°                                    |
| <b>Swivel stand</b>                 | 90°; 45° left; 45° right               |
| <b>Tilt angle</b>                   | 23° up; 5° down                        |
| <b>VESA mounting</b>                | 100 x 100mm                            |
| <b>Cable management system</b>      | yes                                    |

## 05 ACCESSORIES INCLUDED

|        |                                 |
|--------|---------------------------------|
| Cables | power, HDMI                     |
| Other  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                   |   |
|-------------------|---|
| Power supply unit | internal                                  |
| Power supply      | AC 100 - 240V, 50/60Hz                    |
| Power usage       | 16W typical, 0.5W stand by, 0.3W off mode |

## 07 SUSTAINABILITY

|   |   |
|---|---|
| Regulations   | TCO Certified, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | E   |
| REACH SVHC  | above 0.1%: Lead  |

## 08 DIMENSIONS / WEIGHT

|                              |                             |
|------------------------------|-----------------------------|
| Product dimensions W x H x D | 539.5 x 343 (493) x 209,5mm |
| Weight (without box)         | 5.1kg                       |
| EAN code                     | 4948570123841               |

