



## ” Modular 15" all-in-one POS system

### Specifications – P4500

- Fanless, slim POS system for those who value good looks
- Excellent performance thanks to Intel Celeron / Core-i3 / Core-i5
- Exchangeable interfaces for flexible use
- Available with resistive or capacitive touch

		P4500
<b>System</b>	CPU	Intel Celeron 3965U, (Intel Core-i3 7100U, Core-i5-7200U, optional), fanless
	System memory	4 GB SO-DIMM, DDR4, 2133 MHz, max. 16 GB
	Chipset	Intel Kaby Lake platform
	Storage	Min. 500 GB HDD, SSD optional, 1x M.2 (2280) port
	Supported OS	Windows 10
<b>Display</b>	Graphics chip	Intel HD graphics
	LCD size	38.1 cm (15") LCD
	Max. resolution	1024 x 768 pixels
	Brightness	350 nits, LED
	Touch screen	5-wire resistive, PCAP
	Tilt angle	0 to 90°
<b>Interfaces</b>	USB 2.0	up to 4x
	USB 3.0	4x
	Powered USB	1x (optional, 24 V)
	Serial / COM (RJ45)	3x (optional 4x)
	Parallel	-
	LAN	1x Gigabit
	Graphics port	1x VGA, (optional 1x DP)
	Cash drawer port	1x (12V/24V, RJ11)
<b>PSU</b>	Power adapter	90 watts, integrated in the stand
<b>Other</b>	Dimensions (WxDxH)	374 x 265 x 394 mm
	Weight	Ca. 6.6 kg
	Operating temperature	0 to 35 °C
	Certification	CE, RoHS
<b>Options</b>	Mounting options	VESA 100 x 100 mm
	MSR	Yes
	Customer display	Yes (2x20 characters, integrated, pole)
	Customer-facing screen	Yes (8", 10.4", 15", pole)
	Barcode scanner	Yes (1D, 2D)
	Waiter's lock	Yes (iButton)
	RFID	Yes (MiFare)
	Colour	Black
	UPS	Optional
	Interface options	In addition to the standard interfaces, the following options are available: <b>Option A</b> (2x USB 2.0, 1x UPS, 1x audio) <b>Option B</b> (1x UPS, 1x COM (RJ45 with DC 5V/12V), 1x audio) <b>Option C</b> (1x 24 V Powered USB, 2x USB 2.0, 1x microphone in, 1x audio) <b>Option E</b> (4x USB 2.0, 1x COM (RJ45 with DC 5V/12V))*

\*factory default

Your partner