



## Bluetooth Speakerphone for meeting rooms

The omnidirectional audio pickup from up to 3 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01M the perfect choice for medium meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this elegant speaker can be paired with up to 3 devices at the same.



#### **Omnidirectional**

The UC SPK01M supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



### High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



#### Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



## Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

#### **SPECIFICATION**

**Speaker** 

Maximum sound 85dB pressure level

> Distortion ≦1%

75dB

Signal to noise ratio

Frequency range 150Hz ~ 16kHz

Microphone

Number of x3

microphone arrays

Voice pickup range 3m (radius)

Frequency range 150Hz ~ 7.5kHz

**Connectivity & Button operations** 

USB Type C x1 (Audio In/Out, Charge 5V/2A)

**AUX** x1 (In/Out, 3.5mm)

Bluetooth 4.2+EDR

Buttons Power, Volume, Blutooth, Mute, Answer/Hang up

**Accessories & Battery** 

USB (type A to C) yes

cable

Audio cable yes

Battery capacity 7.4V/2200mAh

Charging wired 5V/2A

Battery life on a 8 hours

single charge

**SUSTAINABILITY** 

Regulations CE, RoHS support, ErP, WEEE, REACH

**DIMENSIONS / WEIGHT** 

Weight (without box) 0.39kg

**EAN code** 4948570033034

**RELATED INFORMATION** 

Related products UC CAM120ULB-1, UC CAM120UL-1, UC CAM180UM-1, UC CAM80UM-1, UC

CAM75FS-1, UC SPK01L



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **IIYAMA CORPORATION. ALL RIGHTS RESERVED** 





# Bluetooth Speakerphone for large meeting rooms

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.



#### **Omnidirectional**

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



### High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



#### Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



# Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

#### **SPECIFICATION**

**Speaker** 

Maximum sound 85dB pressure level

Distortion ≦4%

Signal to noise ratio 80dB

Frequency range 150Hz ~ 16kHz

Microphone

Number of x6

microphone arrays

Voice pickup range 5m (radius)

Frequency range 150Hz ~ 8kHz

**Connectivity & Button operations** 

USB Type C x1 (Audio In/Out, Charge 5V/2A)

AUX x1 (In/Out, 3.5mm, DaisyChain)

Bluetooth 4.2+EDR

Buttons Power, Volume, Blutooth, Mute, Answer/Hang up

**Accessories & Battery** 

Bluetooth receiver yes

USB (type A to C) yes cable

Audio cable yes

Battery capacity 7.4V/2200mAh

Charging wired 5V/2A, wireless 5W

Battery life on a 8 hours single charge

**SUSTAINABILITY** 

Regulations CE, RoHS support, ErP, WEEE, REACH

**DIMENSIONS / WEIGHT** 

Weight (without box) 0.4kg

EAN code 4948570033041

**RELATED INFORMATION** 

Related products UC CAM120ULB-1, UC CAM120UL-1, UC CAM180UM-1, UC CAM80UM-1, UC

CAM75FS-1, UC SPK01M

— GALLERY ————		
All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED		